NATIONAL BUREAU OF STANDARDS REPORT

5224

STAIN INDICES OF TWENTY-ONE ASPHALTS

FIRST SUPPLEMENT TO NBS REPORT NO. 4732 REPORT ON THE EVALUATION OF TWENTY-ONE COATING-GRADE ROOFING ASPHALTS

bу

Sidney H. Greenfeld and Shigeru Ishihara



U. S. DEPARTMENT OF COMMERCE NATIONAL BUREAU OF STANDARDS

U. S. DEPARTMENT OF COMMERCE

Sinclair Weeks, Secretary

NATIONAL BUREAU OF STANDARDS

A. V. Astin, Director



THE NATIONAL BUREAU OF STANDARDS

The scope of activities of the National Bureau of Standards at its headquarters in Washington, D. C., and its major field laboratories in Boulder, Colorado, is suggested in the following listing of the divisions and sections engaged in technical work. In general, each section carries out specialized research, development, and engineering in the field indicated by its title. A brief description of the activities, and of the resultant reports and publications, appears on the inside back cover of this report.

WASHINGTON, D. C.

Electricity and Electronics. Resistance and Reactance. Electron Tubes. Electrical Instruments. Magnetic Measurements. Dielectrics. Engineering Electronics. Electronic Instrumentation. Electrochemistry.

Optics and Metrology. Photometry and Colorimetry. Optical Instruments. Photographic Technology. Length. Engineering Metrology.

Heat and Power. Temperature Physics. Thermodynamics. Cryogenic Physics. Rheology and Lubrication. Engine Fuels.

Atomic and Radiation Physics. Spectroscopy. Radiometry. Mass Spectrometry. Solid State Physics. Electron Physics. Atomic Physics. Nuclear Physics. Radioactivity. X-rays. Betatron. Nucleonic Instrumentation. Radiological Equipment. AEC Radiation Instruments.

Chemistry. Organic Coatings. Surface Chemistry. Organic Chemistry. Analytical Chemistry. Inorganic Chemistry. Electrodeposition. Gas Chemistry. Physical Chemistry. Thermochemistry. Spectrochemistry. Pure Substances.

Mechanics. Sound. Mechanical Instruments. Fluid Mechanics. Engineering Mechanics. Mass and Scale. Capacity, Density, and Fluid Meters. Combustion Controls.

Organic and Fibrous Materials. Rubber. Textiles. Paper. Leather. Testing and Specifications. Polymer Structure. Organic Plastics. Dental Research.

Metallurgy. Thermal Metallurgy. Chemical Metallurgy. Mechanical Metallurgy. Corrosion. Metals Physics.

Mineral Products. Engineering Ceramics. Glass. Refractories. Enameled Metals. Concreting Materials. Constitution and Microstructure.

Building Technology. Structural Engineering. Fire Protection. Heating and Air Conditioning. Floor, Roof, and Wall Coverings. Codes and Specifications.

Applied Mathematics. Numerical Analysis. Computation. Statistical Engineering. Mathematical Physics.

Data Processing Systems. SEAC Engineering Group. Components and Techniques. Digital Circuitry. Digital Systems. Analogue Systems. Application Engineering.

• Office of Basic Instrumentation

• Office of Weights and Measures

BOULDER, COLORADO

Cryogenic Engineering. Cryogenic Equipment. Cryogenic Processes. Properties of Materials. Gas Liquefaction.

Radio Propagation Physics. Upper Atmosphere Research. Ionospheric Research. Regular Propagation Services. Sun-Earth Relationships.

Radio Propagation Engineering. Data Reduction Instrumentation. Modulation Systems. Navigation Systems. Radio Noise. Tropospheric Measurements. Tropospheric Analysis. Radio Systems Application Engineering.

Radio Standards. Radio Frequencies. Microwave Frequencies. High Frequency Electrical Standards. Radio Broadcast Service. High Frequency Impedance Standards. Calibration Center. Microwave Physics. Microwave Circuit Standards.

NATIONAL BUREAU OF STANDARDS REPORT

NBS PROJECT 1004-11-1017

April 1, 1957

NBS REPORT 5224

STAIN INDICES OF TWENTY-ONE ASPHALTS

FIRST SUPPLEMENT TO NBS REPORT NO. 4732 REPORT ON THE EVALUATION OF TWENTY-ONE COATING-GRADE ROOFING ASPHALTS

by

Sidney H. Greenfeld

and

Shigeru Ishihara

Research Associates Asphalt Roofing Industry Bureau

Floor, Roof and Wall Coverings Section Building Technology Division

> Jointly Sponsored by Asphalt Roofing Industry Bureau and National Bureau of Standards

IMPORTANT NOTICE

NATIONAL BUREAU OF S' intended for use within the to additional evaluation and listing of this Report, either the Office of the Director, N however, by the Governmen to reproduce additional cop

Approved for public release by the rmally published it is subjected Director of the National Institute of Standards and Technology (NIST) on October 9, 2015.

progress accounting documents , reproduction, or open-literature sion is obtained in writing from Such permission is not needed, prepared if that agency wishes



U. S. DEPARTMENT OF COMMERCE NATIONAL BUREAU OF STANDARDS



STAIN INDICES OF TWENTY-ONE ASPHALTS

FIRST SUPPLEMENT TO NBS REPORT NO. 4732

REPORT ON THE EVALUATION OF TWENTY-ONE

COATING-GRADE ROOFING ASPHALTS

by

Sidney H. Greenfeld

and

Shigeru Ishihara

ABSTRACT

The stain indices of the 21 asphalts discussed in NBS Report No. 4732 were measured in accordance with A.S.T.M. Procedure D1328-54T. The indices ranged from 4 to 26. No correlation was found between stain index and penetration, softening point or durability. Reasons for this lack of correlation are discussed.

1. INTRODUCTION

On 1 July 1956 a report was sent to the Research Committee describing the properties and weathering characteristics of 21 1/ coating-grade roofing asphalts. Subsequent work on the mechanism of the weathering of asphalt indicated that one phase of weathering was related to the ability of some of the components of the maltenes to migrate to the surface of the exposed coating and

^{1/ &}quot;Report on the Evaluation of Twenty-One Coating-Grade Roofing Asphalts", NBS Report No. 4732, 1 July 1956.



react with oxygen in the presence of light. It was proposed to investigate the use of the stain index determination, ASTM D1328-54T (Staining Properties of Asphalts), as a measure of the migration because it measures the movement of some of the component oils to the surface of the asphalt.

2. EXPERIMENTAL

The apparatus and conditions of test are described in ASTM D1328-54T. $\frac{2}{}$

The asphalts are those discussed in detail in NBS Report No. 4732.

3. RESULTS AND DISCUSSION

The results, the average of two determinations differing by no more than two papers, of the stain index determinations are compiled in Table 1, along with some of the other characteristics of the 21 asphalts. The stain indices varied from 26 for Ambit asphalt to 4 for C810. However, except for the highest and lowest two, all of the indices fell within the range of 10 to 20. Thus, the stain index, like many of the other attributes of blown asphalts, appears to be more characteristic of the type of material than of any individual specimen of that type, and an average of 15 ±5 papers seems to be characteristic of air-blown coating-grade asphalts.

^{2/}ASTM D1328-54T, Staining Properties of Asphalt, 1690-1694, Part 3 of ASTM Book of Standards, 1955.



hr. 11	$1 \infty \land \cup \cup$	4
LOSS 1400- 22- Cyc	N 00 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	(
Dura- bility 51-90 Cycle	80 + 80 + 80 + 40 + 60 + 60 + 60 + 60 + 60 + 60 + 6	
Sp. Gr. at 77	000000000000000000000000000000000000000	1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
Pen, Index $\overline{\mathbf{b}}'$		4
Pen. 115	WNNN YWWN WN WN TRUMN WTTN NO CON WN TRUMN	9
Pen.	t & & & & & & & & & & & & & & & & & & &	71
Pen. 32	04111111111111111111111111111111111111	E G
Softening Point	66068501966885516 192201966885516 2022019822516 2022019822516	OCCER MINON
Stain Indexa/	t 80 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	- C
Asphalt	bit 175 175 100 100 100 100 100 100 100 10	a/c+c; Twac;

Numbers in parentheses represent dark oil movement b/Fenetration Index from J. P. Pfeiffer and P. M. Van Doormal, "Classifying Asphalts by Means of Penetration Index", National Petroleum News, Tech. Ed., Feb. 23, 1938. $\frac{a}{a}$ /Stain Index according to ASTM D1328-54T. by daylight observation.



The processing of the four asphalts outside of this range differed in some respects from that of the other asphalts.

Ambit (S.I. = 26) was catalytically blown; Cl175 (S.I. = 24)

was reconstituted with reclaimed lube stock; Mexico #12

(S.I. = 8) was not fully blown (S.P. = 196°F); and C810

(S.I. = 4) was steam reduced to a penetration of 20/30 before blowing. Although the asphalt designated "Catalytic" (S.I. = 14) was also catalytically blown (from a Lagunillas flux), its properties fell within the normal range.

The stain index represents the farthest penetration of the aromatic white oils, as observed by their fluorescence under ultraviolet light. It is believed that during weathering the oils, both light and dark, migrate to the surface of the asphalt, where they are degraded in the presence of light. However, the dark oils are consumed more rapidly than the white oils during normal weathering. Hence, the movement of the dark oils is also of interest. The numbers in parentheses in column 2 of Table 1 represent the farthest movement of the dark oils during the stain index determination. The dark oils stained between two and six, usually four, papers less than the white oils. Because diffusion varies with the square root of the molecular weight, one would expect the dark oils, because of their higher molecular weight, to diffuse less than the white oils under the same conditions. This qualitative deduction and observation are



	<u>C210</u>	<u>M200</u>
White Oils	450	500
Dark Oils	745	900

The ratio of the square roots of the molecular weights of the light and dark oils of C210 is 0.778 and that for those of M200 is 0.746, whereas, the ratios of the papers stained are 0.724 and 0.702, for the two asphalts, respectively. Considering the tolerances in both determinations, this agreement is very good.

However, when an attempt is made to compare these two asphalts or to correlate stain index with the usual rheological properties or durability, difficulties are encountered. Asphalt M200 contains higher molecular weight oils and also has a higher stain index. There also seems to be no relation between stain index and penetrations, penetration index or softening point, the rheological properties by which asphalts are usually characterized. The reasons for this lack of correlation, especially in a qualitative sense, are not clear, for it would be expected that the softer, higher-penetration asphalts would have more of the light, more

^{3/&}quot;The Chemical Changes Occurring During the Degradation of Two Coating Asphalts", N.B.S. Report No. 4861, 1 October 1956.

fluid oils and, consequently, a higher stain index. Apparently, the forces that hold an asphalt together, i.e., the ability of the asphaltenes to hold on to the oils, are sufficiently strong to distort the effects of diffusion.

This property is also related to the durability of asphalt, for it has been observed that it is very difficult to separate the maltenes from the asphaltenes in asphalts that weather well. However, there is no apparent correlation between durability, as presently determined, or weight loss, and stain index.

In summary, it may be concluded that there is no apparent correlation between stain index and durability, weight loss, or any of the rheological properties of coating-grade asphalts normally measured.



THE NATIONAL BUREAU OF STANDARDS

Functions and Activities

The functions of the National Bureau of Standards are set forth in the Act of Congress, March 3, 1901, as amended by Congress in Public Law 619, 1950. These include the development and maintenance of the national standards of measurement and the provision of means and methods for making measurements consistent with these standards; the determination of physical constants and properties of materials; the development of methods and instruments for testing materials, devices, and structures; advisory services to Government Agencies on scientific and technical problems; invention and development of devices to serve special needs of the Government; and the development of standard practices, codes, and specifications. The work includes basic and applied research, development, engineering, instrumentation, testing, evaluation, calibration services, and various consultation and information services. A major portion of the Bureau's work is performed for other Government Agencies, particularly the Department of Defense and the Atomic Energy Commission. The scope of activities is suggested by the listing of divisions and sections on the inside of the front cover.

Reports and Publications

The results of the Bureau's work take the form of either actual equipment and devices or published papers and reports. Reports are issued to the sponsoring agency of a particular project or program. Published papers appear either in the Bureau's own series of publications or in the journals of professional and scientific societies. The Bureau itself publishes three monthly periodicals, available from the Government Printing Office: The Journal of Research, which presents complete papers reporting technical investigations; the Technical News Bulletin, which presents summary and preliminary reports on work in progress; and Basic Radio Propagation Predictions, which provides data for determining the best frequencies to use for radio communications throughout the world. There are also five series of nonperiodical publications: The Applied Mathematics Series, Circulars, Handbooks, Building Materials and Structures Reports, and Miscellaneous Publications.

Information on the Bureau's publications can be found in NBS Circular 460, Publications of the National Bureau of Standards (\$1.25) and its Supplement (\$0.75), available from the Superintendent of Documents, Government Printing Office. Inquiries regarding the Bureau's reports and publications should be addressed to the Office of Scientific Publications, National Bureau of Standards, Washington 25, D. C.

